



# ORCON AEROSPACE

Aerospace Division

## Orcotape® OT-57CW Repair and Fabrication Tape

### TAPE SPECIFICATIONS

**ORCOTAPE® OT-57CW** is a pressure-sensitive, reinforced polyvinyl fluoride tape used in the fabrication, repair and installation of thermal/acoustic aircraft insulation blankets.

PROPERTIES	TEST METHOD		SPECIFICATION
<b>COLOR</b>			Translucent White
<b>WEIGHT</b>	Fed Std 191, Method 5041		3.3 oz/sq yd, max 112 g/sq m, max
<b>PEEL STRENGTH</b>	ASTM D903		2.0 lbs/inch, min
<b>TENSILE STRENGTH</b>	BMS 5-157		10.0 lbs/inch, min
<b>FLAMMABILITY, TAPE ONLY</b>	FAR Part 25 App. F Part I		Pass
<b>FLAMMABILITY, RADIANT PANEL TEST</b>	FAR Part 25 App. F Part VI		Pass
<b>SPECIFICATIONS</b>	FAR 25.853, FAR 25.855, FAR 25.856 (a); MMS-01-001 Type 1		
<b>PACKAGING</b>	Standard roll length Standard width	60 yards (55 meters) 2 and 3 inches (5.1 and 7.6 cm) Custom widths available on request	

Note: To the best of our knowledge, information in the document is accurate. However, ORCON Corporation does not assume liability for the accuracy or completeness of the information provided. ORCOTAPE is a registered trademark of ORCON Corporation. This revision replaces all previous revisions. Revised 06/2007.