



| ORCOFILM® | Application Specifications | Features |
|---|-------------------------------|---|
| PEEK Films | | |
| EN-158C | FAR 25.856(a) | Metalized & heat-sealable |
| POLYVINYL FLUORIDE (Tedlar®) FILMS | | |
| AN-54W | BMS8-377, BMS8-360, DMS 2450C | Metalized, stitchable and heat-sealable |
| AN-57W | BMS8-377, BMS8-360 | Metalized and stitchable ONLY |
| POLYIMIDE FILMS | | |
| KN-201 | DMS 2450C | Amber and heat-sealable |
| KN-202 | DMS 2450C | Delustered and heat-sealable |
| Previous Generation ORCOFILM® Replacements | | |
| | Replaces | Prior ORCOFILM® |
| EN-158C (PEEK) | >>> | AN-58A |
| AN-57W | >>> | AN-36W |
| EN-158C (PEEK) | >>> | AN-41DA |
| AN-54W | >>> | AN-57W |
| AN-54W | >>> | AN-49W |
| AN-54W | >>> | AN-51W |
| AN-54W | >>> | AN-4C |
| AN-54W | >>> | AN-16R |
| AN-54W | >>> | AN-18R |
| AN-54W | >>> | AN-19W |
| KN-201, KN-202 | >>> | KN-80 |